

# 1/2" Security Chain Link Mesh Variables 11-1/2 ga to 9 ga

1/2" Mesh Wind & Weight Values				
Gauge	Dia (in)	$\epsilon$	$C_{fw}$	$D_m$ (psf)
5	0.207	-	-	-
6	0.192	-	-	-
8	0.162	-	-	-
9	0.148	0.43	1.5	3.3
10	0.135	0.40	1.5	2.6
11	0.120	0.37	1.5	1.8
11-1/2	0.113	0.35	1.5	1.5

$\epsilon$  = solidity ratio for chain link  
 $\epsilon'$  = solidity ratio for iced chain link  
 $C_{fw}$  = wind force coefficient  
 $C_{fi}$  = wind on ice force coefficient  
 $D_m$  = estimated weight of chain link mesh  
 Check with supplier for actual weight  
 $D_i$  = estimated weight of ice (includes 0.7 ASD factor)  
 The values below are only valid for Risk Category I and  $K_{zt} = 1.0$   
 For ice thickness not shown below, round up to next nearest value

1/2" Security Mesh (all gauges) Estimated Ice Loading Risk Category I $K_{zt} = 1.0$												
ASCE 7-10 Nominal Ice Thickness, t (in)	Fence Height, h											
	5'			10'			15'			20'		
	$\epsilon'$	$C_{fi}$	$D_i$ (psf)	$\epsilon'$	$C_{fi}$	$D_i$ (psf)	$\epsilon'$	$C_{fi}$	$D_i$ (psf)	$\epsilon'$	$C_{fi}$	$D_i$ (psf)
0.25	1.00	See solid wall $C_{fi}$ table below	2.5	1.00	See solid wall $C_{fi}$ table below	2.7	1.00	See solid wall $C_{fi}$ table below	2.9	1.00	See solid wall $C_{fi}$ table below	3.0
0.50	1.00		5.5	1.00		5.9	1.00		6.1	1.00		6.3
0.75	1.00		8.2	1.00		8.8	1.00		9.2	1.00		9.5
1.00	1.00		11.0	1.00		11.8	1.00		12.3	1.00		12.6
1.25	1.00		13.7	1.00		14.7	1.00		15.3	1.00		15.8
1.50	1.00		16.5	1.00		17.7	1.00		18.4	1.00		18.9
ASCE 7-16 Nominal Ice Thickness, t (in)	Fence Height, h											
	5'			10'			15'			20'		
	$\epsilon'$	$C_{fi}$	$D_i$ (psf)	$\epsilon'$	$C_{fi}$	$D_i$ (psf)	$\epsilon'$	$C_{fi}$	$D_i$ (psf)	$\epsilon'$	$C_{fi}$	$D_i$ (psf)
0.25	0.93	See solid wall $C_{fi}$ table below	1.1	0.95	See solid wall $C_{fi}$ table below	1.2	0.96	See solid wall $C_{fi}$ table below	1.2	0.97	See solid wall $C_{fi}$ table below	1.3
0.50	1.00		2.5	1.00		2.7	1.00		2.9	1.00		3.0
0.75	1.00		4.1	1.00		4.4	1.00		4.5	1.00		4.7
1.00	1.00		5.5	1.00		5.9	1.00		6.1	1.00		6.3
1.25	1.00		6.9	1.00		7.4	1.00		7.7	1.00		7.9
1.50	1.00		8.2	1.00		8.8	1.00		9.2	1.00		9.5
1.75	1.00		9.6	1.00		10.3	1.00		10.7	1.00		11.0
2.00	1.00		11.0	1.00		11.8	1.00		12.3	1.00		12.6
2.25	1.00		12.4	1.00		13.3	1.00		13.8	1.00		14.2
2.50	1.00		13.7	1.00		14.7	1.00		15.3	1.00		15.8
ASCE 7-22 Nominal Ice Thickness, t (in)	Fence Height, h											
	5'			10'			15'			20'		
	$\epsilon'$	$C_{fi}$	$D_i$ (psf)	$\epsilon'$	$C_{fi}$	$D_i$ (psf)	$\epsilon'$	$C_{fi}$	$D_i$ (psf)	$\epsilon'$	$C_{fi}$	$D_i$ (psf)
0.25	0.98	See solid wall $C_{fi}$ table below	1.4	0.99	See solid wall $C_{fi}$ table below	1.5	1.00	See solid wall $C_{fi}$ table below	1.6	1.00	See solid wall $C_{fi}$ table below	1.6
0.50	1.00		3.3	1.00		3.6	1.00		3.7	1.00		3.9
0.75	1.00		5.1	1.00		5.5	1.00		5.7	1.00		5.9
1.00	1.00		6.9	1.00		7.4	1.00		7.7	1.00		7.9
1.25	1.00		8.6	1.00		9.2	1.00		9.6	1.00		9.9
1.50	1.00		10.3	1.00		11.0	1.00		11.5	1.00		11.8
1.75	1.00		12.0	1.00		12.9	1.00		13.4	1.00		13.8
2.00	1.00		13.7	1.00		14.7	1.00		15.3	1.00		15.8
2.25	1.00		15.5	1.00		16.6	1.00		17.2	1.00		17.8
2.50	1.00		17.2	1.00		18.4	1.00		19.2	1.00		19.7

Solid Wall Case A $C_{fi}$ values for line posts away from ends and corners for $\epsilon' > 0.7$										
Only for $s/h = 1$	B/s									
	1	2	3	4	5	6	7	8	9	$\geq 10$
	1.45	1.40	1.38	1.35	1.35	1.34	1.33	1.32	1.31	1.30

B = Length of fence segment being considered  
 s = Solid height of fence  
 h = Overall height of fence  
 $s/h = 1$  assumes ice bridges any gap at the bottom of the fence and  $s = h$   
 For conditions not show above, see the ASCE §29 Solid Wall Table  
Round B/s value down to nearest value shown on the chart